

Sagemcom

Sagemcom F@st 3896

Wi-Fi 6 triple-play home gateway



Sagemcom F@st 3896 is a broadband gateway providing multi-gigabit broadband Internet access through DOCSIS 3.1 and 3.0 cable networks. With Sagemcom F@st 3896 and the associated set-top-boxes, the user gets access to 3-play services with a high level of quality:

- Up to 5Gbps Downlink and 2 Gbps Uplink throughput over DOCSIS
- Dual band dual concurrent Wi-Fi 6 Access Point in 2.4 and 5 GHz bands
- High quality Voice over IP communication based on the MGCP protocol as well as on SIP (option)
- Content sharing with embedded DLNA Server (option) and USB host 3.0 port (option)

Sagemcom F@st 3896 software is available in two versions either in-house field proven Sagemcom SWAN™ solution either RDK-B well-known solution defined by cable industry for broadband gateways..

SEAMLESS MULTI DEVICE CONNECTION

With Sagemcom F@st 3896, end user can connect all its IT network devices (mobile phones, tablets, computers, printers, gaming devices, fixed or DECT phones, ...) easily and simultaneously over all the available interfaces: Wi-Fi 6, 2.5 Gigabit Ethernet, Multi-Gigabit Ethernet, USB host 3.0, FXS. The F@st 3896 also optionally includes an integrated bonded MoCA 2.0 interface which enables the gateway to provide connectivity to STB and client devices connected within the home.

TOP CLASS WIRELESS INTERFACE

Sagemcom F@st 3896 offers a superfast "dual band dual concurrent" and reliable wireless LAN connection. It includes high efficient Wi-Fi 6 interfaces on both bands: 4x4 11ax for 5GHz, 3x3: 3x3 or 4x4 11ax for 2.4GHz with advanced multi-user wireless technology. Thanks to its easy install program, a home network without in house cabling can be easily built. Sagemcom F@st 3896 also features the latest WPA3 security mechanism while being compatible with WPA/WPA2 older scheme. In addition, in order to facilitate the configuration it offers the automatic radio channel selection and WPS for security key exchange.

RICH VOICE CONTENT

Sagemcom F@st 3896 integrates a scalable, field proven solution of Wi-Fi community, with options at several levels:

- Traffic isolation: L2TP and GRE tunnels
- QoS: Minimum guaranteed bandwidth for Home user
- Priority on traffic (Home user: higher priority)
- Wi-Fi: Maximum number of connected Hotspot Users

FULLY FEATURED IP ROUTER

Sagemcom F@st 3896 supports the most up-to-date IP services applicable to residential gateway. It enables IPV6 network either in Dual Stack mode or in DS Lite mode.

EFFICIENT FIREWALL

Sagemcom F@st 3896 integrates the most up-to-date firewall tools:

- Stateful Packet Inspection
- Complete address/port/protocol filtering
- VPN pass through: PPTP or IPsec

REMOTE MANAGEMENT: TR-069 AND SNMP AGENTS

Sagemcom F@st 3896 offers a robust SNMP Agent ensuring full remote service provisioning and resilient upgrade. The home gateway also offers a field proven TR-069 agent.

MULTI-PLAY QUALITY OF SERVICE

Sagemcom F@st 3896 associates comprehensive QoS techniques for double and triple architectures achieving a complete management of the QoS with the guaranty to use simultaneous services with a good level of performance. Dedicated CPU cores for Networking & Voice and for Multimedia Applications enable to guarantee high performance.

SWAN™, A RICH AND AGILE MIDDLEWARE

With in-house SWAN™ middleware version, Sagemcom F@st 3896 benefits from a software solution largely deployed on the field. It does natively support IPV6. The fully featured dual stack IP v4/v6 of SWAN™ middleware ensures to the F@st 3896 its readiness for all major scenario of IPV6 network migration. SWAN™ modular architecture allows easy third parties application integration for operator to easily differentiate: GUI, Web services or even new features developed over SWAN™ SDK.

WHOLE HOME WI-FI AGENT INTEGRATED

Sagemcom F@st 3896 embeds Sagemcom Whole Home Wi-Fi agent ensuring the following services:

- 802.11k/v support
- Bandsteering 2.4 GHz / 5 GHz
- Wi-Fi performances reporting to cloud
- Troubleshooting report

VARIANTS	F@st 3896 4x4	F@st 3896 3x3	F@st 3896UM 4x4
LAN	1 x 2.5GEth port	4 x 1GEth ports	1 X 2.5GEth port
	3 x 1GEth ports		3 x 1GEth ports 1 x Moca 2.0 port
WLAN	802.11ax	802.11ax	802.11ax
	@ 2.4GHz 4x4 @ 5GHz 4x4	@ 2.4GHz 3x3 @ 5GHz 4x4	@ 2.4GHz 4x4 @ 5GHz 4x4

Technical features

INTERFACES

- Network:
 - DOCSIS 3.1 2x2
 - DOCSIS 3.0 with channel bonding up to 32x8
 - Switchable diplexer 85MHz / 204MHz (option)
 - Backward compatible with DOCSIS 1.0/2.0 and 2.0b
 - Compatible with EuroDOCSIS and US DOCSIS frequencies
- User:
 - Wi-Fi: Wi-Fi 6 access point in 2.4 GHz and 5 GHz (see detail in configuration table)
 - Ethernet:
 - Eth 100/1000/2500 Base-T
 - Eth 10/100/1000 Base-T
 - MoCA (optional)
 - Bonded MoCA 2.0
 - Full backward compatibility to MoCA 1.1 ; Support for up to 16 MoCA network nodes ; Throughput up to 800 Mbps
 - Expanded range of operating frequencies - 1150 MHz to 1650 MHz
 - Supports both parameterized and prioritized QoS
 - 1 USB host 3.0 for Accessories (option)
 - 2 FXS (option)

- IGMP Proxy/snooping
- Firewall:
 - Address, port and protocol filtering
 - State full Packets Inspection
- Quality of service: DiffServ
- L2TP

VOICE OVER IP (VOIP)

- Multi FxS management, up-to 2 VOIP lines
- Protocol NCS, MGCP or SIP (PacketCable 1.5 and PacketCable 2.0 supported)
- Voice coding:
 - G711 (64 kbps)
 - G729 (8 kbps)

REMOTE MANAGEMENT

- Firmware upgrade by TFTP or HTTP
- Auto provisioning and remote configuration
- SNMP
- TR-069
- Advanced voice supplementary services

ELECTRICITY SAFETY

- Compliant with EN 60 950, EN 41003

ENVIRONMENT

- Operating temperature: 5°C to 40 °C
- EMC: 89/336EEC, EN 55022 Class B, EN 55024
- Support IEEE 11b/g/n/ax main features (2.4 GHz)
- Support IEEE 11a/n/ac/ax main features (5 GHz)
- CE

PHYSICAL FEATURES

- External Power supply
- Size (L x D x H in mm): 190 x 65 x 222 to 235 (with foot)
- Weight (g): 950g

All rights reserved. The information and specifications included are subject to change without prior notice. Sagemcom Broadband tries to ensure that all information in this document is correct, but does not accept liability for error or omission. Non contractual document. All trademarks are registered by their respective owners. Simplified joint stock company Capital 58 251 417,36 Euros - 440294510 RCS Nanterre. 07/2020

Sagemcom Broadband SAS

Headquarters: 250, route de l'Empereur
92848 Rueil-Malmaison Cedex | FRANCE

Tel: +33 (0)1 57 61 10 00 | Fax: +33 (0)1 57 61 10 01

www.sagemcom.com

Sagemcom