



OceanStor V5 Mid-Range Hybrid Flash Storage Systems

OceanStor 5300, 5500, 5600, and 5800 V5 mid-range hybrid flash storage systems (OceanStor V5 mid-range hybrid flash storage for short) are Huawei's enterprise-class hybrid flash storage. With a cloud-ready operating system, industry-leading hardware platform, and intelligent management software, OceanStor V5 mid-range hybrid flash storage delivers top-of-the-line functionality, performance, efficiency, reliability, and ease of use. It fully satisfies the data storage requirements of large-database OLTP/OLAP, file sharing, cloud computing, and many other applications, and thereby is applicable to sectors such as government, finance, telecommunications, energy, and media. OceanStor V5 mid-range hybrid flash storage also provides a wide range of efficient and flexible backup and disaster recovery (DR) solutions to ensure business continuity and data security, delivering excellent storage services.

Product Highlights

Multi-level Convergence

Powered by the latest OceanStor OS, OceanStor V5 mid-range hybrid flash storage provides converged and unified resource pools with the agility of resource scheduling, enabling free data mobility and helping enterprise IT architectures evolve to cloud-based architectures.

- **Convergence of all types of flash storage:** Huawei has the most complete flash product portfolio and supports interconnection between different types, levels, and generations of flash storage. Convergence of data, management, and O&M empowers million-level IOPS performance and low-latency flash storage arrays, while ensuring the long-term reliability of SSDs.
- **Convergence of SAN and NAS:** SAN and NAS are converged to provide elastic storage, improve storage resource utilization, and reduce the total cost of ownership (TCO). The new OceanStor V5 mid-range hybrid flash storage not only converges SAN and NAS to support multiple types of services, but also provides industry-leading SAN and NAS performance and functions.
- **Convergence of storage resource pools:** The built-in heterogeneous virtualization function enables OceanStor V5 mid-range hybrid flash storage to take over the storage arrays of different levels, types, and models from other mainstream vendors, and integrate them into a unified resource pool. This eliminates data silos, achieves unified resource management, and enables automated service orchestration. In addition, data can be automatically migrated from third-party storage to Huawei storage without interrupting services. Huawei's automatic migration tool reduces the migration time by 60% on average.

Convergence of multiple data centers: The converged active-active solution converges gateways, quorum devices, and networks to make the networking simpler. The HyperMetro active-active solution, in combination with HyperVault 3DC, further guarantees the continuity of core services. Active-active data center deployment can be smoothly upgraded to the geo-redundant 3DC layout to achieve the highest level of service continuity protection. Customers can also deploy hierarchical data centers for the purpose of centralized disaster recovery. Currently, Huawei storage supports the backup of data from 64 subordinate data centers to a central data center.

Excellent Performance

Meeting performance requirements for core enterprise services

- **Flash-oriented storage architecture:** OceanStor V5 mid-range hybrid flash storage employs a flash-oriented system architecture, based on the flash convergence technology, CPU scheduling, cache, RAID, and interworking between the OceanStor OS and disk drives that are specially designed to suit flash memory. OceanStor V5 mid-range hybrid flash storage can intelligently sense HDDs and SSDs, automatically distinguish between media types, and dynamically select the optimal algorithms to provide a stable I/O response time that is shorter than 1 ms in the event of massive service access requests, thereby ensuring the optimal performance of critical applications. (In the high-end storage industry, the average I/O response time is about 5 to 10 ms).
- **Industry-leading flash-oriented specifications:** OceanStor V5 mid-range hybrid flash storage employs multi-core processors, cutting-edge PCIe 3.0 buses, 12 Gbit/s SAS 3.0 high-speed disk ports, and a variety of front-end ports such as 32 Gbit/s Fibre Channel and 100 Gbit/s Ethernet front-end ports. It fully meets requirements for bandwidth-sensitive application scenarios, such as those involving videos and large files.
- **Flexible scalability:** With the scale-out architecture, OceanStor V5 mid-range hybrid flash storage can be equipped with a maximum of 8 controllers, 4 TB of cache, and 2,000 disk drives, providing performance necessary to support customers' ever-increasing data demands and maximizing their return on investment.

Solid Reliability

99.9999% availability at product and solution levels

- **Load balancing among multiple controllers:** OceanStor V5 mid-range hybrid flash storage enables load balancing among controllers and eliminates single points of failure, thereby ensuring high system availability and stable service running. Multiple controllers can be used simultaneously to accelerate services for one host, removing performance bottlenecks of a single controller and doubling performance.
- **Unique rapid data restoration technology:** Innovative block-level virtualization is employed to reduce the time needed to reconstruct 1 TB of data from 10 hours to 30 minutes. Compared with traditional storage systems, OceanStor V5 mid-range hybrid flash storage reduces the risk of data damage caused by disk failures by 95%.
- **A wide range of data protection software:** The Hyper series of data protection software includes snapshot, clone, all-in-one backup, remote replication, and other data protection technologies. They protect user data locally, remotely, inside systems, and across different regions, and achieve 99.9999% availability, maximizing business continuity and data availability.

- Active-active SAN and NAS for core applications:** Huawei takes the lead to launch a converged SAN and NAS active-active solution, ensuring high availability for databases and file services. The gateway-free HyperMetro solution enables load balancing of active-active mirrors and non-disruptive cross-site takeover, ensuring zero loss of core application data and zero service interruption. In addition, HyperMetro can be effortlessly upgraded to the geo-redundant layout with three data centers.

Intelligent Services

Accelerating the cloud transformation of enterprises

- Intelligent O&M:** eService enables cloud-based monitoring, around-the-clock proactive monitoring, minute-level fault sensing, automatic fault reporting, and automatic ticket creation. eService can also automatically inspect every aspect of a device's status, provide cloud-ready evaluation services, automatically analyze workload characteristics, generate an analysis report with one click, recommend storage design schemes, offer intelligent trend prediction, and plan expansion in advance.
- Hybrid cloud solution:** Huawei offers a hybrid-cloud-based storage solution for enterprises, which implements on- and off-premises resource collaboration and data mobility. Public cloud is regarded as a storage tier. Customers can perform cross-cloud data backup and migration, achieving smooth cloud transformation of storage services.

Product Specifications

Name	OceanStor 5300 V5	OceanStor 5500 V5	OceanStor 5600 V5	OceanStor 5800 V5
Controller Enclosure Specifications				
Processor	Multi-core processors			
System cache (expands with the number of controllers)	64 GB to 512 GB	128 GB to 1,024 GB	256 GB to 2,048 GB	512 GB to 4,096 GB
Maximum number of controllers	8	8	8	8
Supported storage protocols	Fibre Channel, iSCSI, NFS, CIFS, HTTP, FTP	Fibre Channel, iSCSI, NFS, CIFS, FTP, HTTP		
Types of front-end ports	8/16/32 Gbit/s Fibre Channel, 1/10/25/40/100	8/16/32 Gbit/s Fibre Channel, 1/10/25/40/100 Gbit/s Ethernet		

Name	OceanStor 5300 V5	OceanStor 5500 V5	OceanStor 5600 V5	OceanStor 5800 V5
	Gbit/s Ethernet			
Type of back-end ports	SAS 3.0 (single port 4 x 12 Gbit/s)			
Maximum number of hot-swappable I/O modules (per controller)	2	2	8	8
Maximum number of front-end ports per controller	20	20	28	28
Maximum number of disks (dual-controller)	1,000	1,200	1,600	2,000
Disk type	SSD, SAS, NL-SAS			
Standalone gateway	Support			
RAID	RAID 0, 1, 3, 5, 6, 10, 50			
Key Software Features				
Data protection software	HyperSnap (snapshot), HyperClone (clone) HyperCopy (copy), HyperMirror (volume mirroring) HyperMetro (active-active arrays), HyperReplication (remote replication) HyperLock (WORM), HyperVault (all-in-one backup)			
Mission-critical business protection	SmartQoS (intelligent service quality control) SmartPartition (intelligent partitioning) SmartCache (intelligent SSD caching)			
Resource efficiency improvement software	SmartMigration (intelligent LUN migration), SmartVirtualization (intelligent heterogeneous virtualization) SmartMulti-Tenant (intelligent multi-tenant), SmartQuota (quota management) SmartDedupe (intelligent deduplication), SmartCompression (intelligent compression) SmartThin (intelligent thin provisioning), SmartTier (intelligent data tiering) SmartMotion (intelligent data motion), SmartErase (intelligent data destruction)			
Storage management software	UltraPath (host multipath), BCManager (DR management) DeviceManager (single-device management software), eSight (centralized O&M management software)			

Name	OceanStor 5300 V5	OceanStor 5500 V5	OceanStor 5600 V5	OceanStor 5800 V5
	eService (remote maintenance management software)			
Virtualization Features				
Heterogeneous virtualization	Consolidates storage resources of mainstream products to manage and allocate storage resources in a flexible and unified manner.			
Block-level virtualization	Enables balanced data distribution and quick fault recovery.			
Physical Specifications				
Power supply	AC: 200 V to 240 V DC: 192 V to 288 V, or -48 V to -60 V			
Dimensions (H x W x D)	2 U controller enclosure: 86.1 mm x 447 mm x 488 mm	2 U controller enclosure: 86.1 mm x 447 mm x 750 mm	3 U controller enclosure: 130.5 mm x 447 mm x 750 mm	
	2 U disk enclosure: 86.1 mm x 447 mm x 490 mm 4 U disk enclosure: 175 mm x 447 mm x 490 mm 4 U HD disk enclosure: 176.5 mm x 446 mm x 790 mm			
Weight	2 U controller enclosure: ≤ 37 kg		3 U controller enclosure: ≤ 50 kg	
	2 U disk enclosure: ≤ 20 kg			
	4 U disk enclosure: ≤ 40 kg			
	4 U HD disk enclosure: ≤ 91 kg			
Operating temperature	5°C to 40°C (altitude: < 1,800 m), 5°C to 35°C (altitude: 1,800 m to 3,000 m)			
Operating humidity	5% RH to 90% RH			

For More Information

To learn more about Huawei storage, please contact your local Huawei office or visit Huawei Enterprise website: <http://e.huawei.com>.



Huawei Enterprise APP



Huawei IT

Copyright © Huawei Technologies Co., Ltd. 2019. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without the prior written consent of Huawei Technologies Co., Ltd.



Trademarks and Permissions



HUAWEI, and  are trademarks or registered trademarks of Huawei Technologies Co., Ltd.

Other trademarks, product, service and company names mentioned are the property of their respective holders.

NO WARRANTY

THE CONTENTS OF THIS MANUAL ARE PROVIDED "AS IS". EXCEPT AS REQUIRED BY APPLICABLE LAWS, NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE MADE IN RELATION TO THE ACCURACY, RELIABILITY OR CONTENTS OF THIS MANUAL.

TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, IN NO CASE SHALL HUAWEI TECHNOLOGIES CO., LTD BE LIABLE FOR ANY SPECIAL, INCIDENTAL, INDIRECT, OR CONSEQUENTIAL DAMAGES, OR LOST PROFITS, BUSINESS, REVENUE, DATA, GOODWILL OR ANTICIPATED SAVINGS ARISING OUT OF, OR IN CONNECTION WITH, THE USE OF THIS MANUAL.

HUAWEI TECHNOLOGIES CO.,LTD.

Bantian Longgang District
Shenzhen 518129, P.R.China
Tel: +86-755-28780808

www.huawei.com