

Data Sheet

PRIMERGY GX2570 M6 GPU Server

Performance oriented server for high-grade AI, Data Science and HPC workloads


PRIMERGY portfolio offers a fantastic blend of systems, solutions and expertise to guarantee maximum productivity, efficiency and flexibility, delivering confidence and reliability. PRIMERGY server systems deliver workload-optimized x86 industry standard servers for any workload and business demand. Since there is no single server solution to meet all these needs, PRIMERGY provides a broad server portfolio consisting of expandable tower servers for remote and branch offices, versatile rack-mount servers, density-optimized multi-node servers as well as GPU accelerated servers optimized for AI. Whatever the size of your business – large enterprise with multiple sites, or a small or medium-sized company with limited space and budget – with the right choice of server, your IT can become the business enabler you have always wanted it to be.

Platinum power supplies (2+2 redundant) provide ample power to run the high-grade workloads. Furthermore, the server supports Fujitsu ISM, to enhance admin productivity and ease server usage across the entire lifecycle.



PRIMERGY GX2570 M6

The Fujitsu Server PRIMERGY GX2570 M6 is an advanced dual socket rack server enhanced with the latest technology high-density GPU configurations to accelerate Artificial Intelligence (AI), Data Science and High Performance Computing (HPC) workloads to extract breakthrough insights from data. This powerful system comes with a high density, next generation 8x NVIDIA A100 SXM4 GPU (80GB) configuration along with up to 2x 3rd Generation Intel® Xeon® Processor Scalable Family CPUs and up to 2TB (32 DIMM) latest generation DDR4 technology plus NVIDIA certified. Designed for delivering high-grade GPU acceleration, the server is meant for demanding use-cases such as Deep Learning (AI) and Data Science deployments, plus other demanding workloads such as HPC. The server is also well-balanced by design, and fields up to 10x storage devices (four can be high-speed NVMe), and up to 10x PCIe Gen4 expansion slots (8x can be assigned for NIC cards for high speed direct access to the GPU). Energy efficient 3000W



Features & Benefits

Main Features	Benefits
<p>Top of the line performance for heavy-duty AI, Data Science and HPC workloads</p> <ul style="list-style-type: none"> 8x NVIDIA A100 SXM4 GPUs (HGX platform) plus 2x 3rd Generation Intel® Xeon® Scalable Processors with up to 2TB memory (32 DIMM slots). 	<ul style="list-style-type: none"> True no-compromise technology with 3rd Generation Intel® Xeon® Scalable Processors, high performance DDR4 memory, NVIDIA A100 80GB GPUs with high-speed interconnects. These servers perform far better across heavy-duty Deep Learning (AI), Data Science and HPC workloads, than regular units. NVIDIA certified testing ensure server is already checked out for multiple use-cases. Drive options include high-speed NVMe, storage and networking controllers, so that the server can be tailored to specific business needs. Versatile PCIe slots allow efficient server upgrade. While essential I/O requirements are also met with dedicated I/O ports. High efficiency power supplies save costs over the server lifecycle, while the provision for N+1 redundancy (in this case 2+2) allows a standby PSU to replace a PSU which has failed, ensuring the server continues working without loss of valuable data or hardware damage, protecting your investment. Administrator confidence as Fujitsu pretests software and hardware. ISM functions include server status and event monitoring, update, inventory and archive management, logging and auditing, floor layout and rack-view, all via an easy to use UI, for easy server administration.
<p>Broad range of flexible hardware configuration options</p> <ul style="list-style-type: none"> Up to 6x high speed SAS/SATA/NVMe drives (front) plus 4 optional NVMe (rear), 10x PCIe Gen4 slots (8x PCIe can field NICs for high speed direct access to 8x GPUs), support for advanced RAID cards, 1x OCP LAN. Additional I/O ports include 2x USB 3.0, 1x VGA. 	
<p>Investment and lifecycle cost protection</p> <ul style="list-style-type: none"> Up to 4x 3000W (2+2) configuration Platinum Power supplies, for high energy efficiency and redundancy. 	
<p>Easy to deploy, use and maintain</p> <ul style="list-style-type: none"> Pre-tested qualified OS support by Fujitsu apart from NVIDIA certifications, support for essential Fujitsu ISM functions. 	

Technical details

PRIMERGY GX2570 M6

Product Type	Dual Socket Rack Server
Mainboard	
Mainboard type	MBD-X12DGO-6
Processor quantity and type	2 x Intel® Xeon® Gold 53xx processor / Intel® Xeon® Gold 63xx processor
Memory slots	32
Memory capacity (min. - max.)	512 GB - 2 TB
Interfaces	
USB 3.x ports	2
Onboard or integrated Controller	
SATA Controller	Intel® C621A
LAN Controller	Dynamic LoM via OCP slot; OCPv3 compliant Optional OCP adaptors: 4 x 1 Gbit/s Ethernet (RJ45) 2 x 10 Gbit/s Ethernet (RJ45) 2 x 10 Gbit/s SFP+ 4 x 10 Gbit/s SFP+ 2 x 25 Gbit/s SFP+ 2x 100 Gbit/s QSFP28
Remote management controller	IPMI 2.0 compatible
Slots	
PCI-Express 4.0 x16	10 x
Slot Notes	8x slots can be used for NIC cards for direct high-throughput GPU access
Drive bays	
Storage drive bays	6x SAS/SATA/NVMe (front)+4 NVMe (rear, optional) x 2.5-inch
General system information	
Number of fans	12
Fan configuration	CPU Node: 8x 1U fans, GPU node: 4x heavy-duty fans
Operating buttons	On/off switch
Status LEDs	Identification (blue)
Operating Systems and Virtualization Software	
Certified or supported operating systems and virtualization software	VMware vSphere™ 8.0 VMware vSphere™ 7.0 SUSE® Linux Enterprise Server 15 Red Hat® Enterprise Linux 8
Operating system release link	http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473
Operating system notes	Use of certified or supported operating systems and virtualization software is subject to proactive acceptance of the respective License Agreements/ EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration.
DC Infrastructure Management	Infrastructure Manager (ISM) Essential Edition Advanced Edition
Server Management	Infrastructure Manager (ISM) Essential Edition Advanced Edition
Floor-stand (W x D x H)	
Rack (W x D x H)	485 x 947 x 175 mm
Height Unit Rack	4 U

Weight notes	Actual weight may vary depending on configuration
Floor-stand (W x D x H)	
Weight	70,7
Environment	
Operating ambient temperature	10 - 35 °C
Operating environment	FTS 04230 – Guideline for Data Center (installation specification)
Operating environment link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe
Electrical values	
Active power (max. configuration)	5,347 W
Heat emission (max. configuration)	19249.2 kJ/h (18244.7 BTU/h)
Compliance	
Product	PRIMERGY GX2570 M6
Global	CB
Europe	CE Class A *
USA/Canada	FCC Class A
Japan	VCCI:V3 Class A + JIS 61000-3-2
Taiwan	BSMI
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

Components

SSD SATA 2.5-inch	SSD SATA, 6 Gb/s, 960 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.5 DWPD
	SSD SATA, 6 Gb/s, 480 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.5 DWPD
	SSD SATA, 6 Gb/s, 240 GB, Read-Intensive, 2.5-inch, enterprise, 1.5 DWPD
	SSD SATA, 6 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.5 DWPD
HDD 2.5-inch	HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
PCIe SSD & SATA DOM SSD	PCIe-SSD SFF, 15.36 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 1.0 DWPD
	PCIe-SSD SFF, 12.8 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD
	PCIe-SSD SFF, 7.68 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 1.0 DWPD
	PCIe-SSD SFF, 6.4 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD
	PCIe-SSD SFF, 3.84 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 1.0 DWPD
	PCIe-SSD SFF, 3.2 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD
	PCIe-SSD SFF, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 1.0 DWPD
PCIe-SSD SFF, 1.6 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD	
Communication, Network	InfiniBand HCA 1 x 200Gb/s PCIe x16 QSFP for the US market max. one IB HCA 200Gb controller can be installed (Mellanox)
	InfiniBand HCA 2 x 200Gb/s PCIe x16 QSFP for the US market max. one IB HCA 200Gb controller can be installed (Mellanox)
Notes	
Compatibility	If and to the extent a list of components or certain compatibilities are specified in the product data sheet, these component lists and compatibility specifications are exhaustive. Using deviating or other system components and applications together with the product may but does not necessarily have to lead to compatibility problems. A final statement and/or commitment on the compatibility of such deviating or other system components and applications can only be provided after a corresponding verification through a dedicated compatibility testing.

Notes

Continuity management	The product may in connection with and depending on the specific configuration include elements to support time- and performance-critical applications, however high availability (e.g., 99.9999%) and failsafe performance is not a standalone product feature. If and to the extent the product is to be used in such business-critical environments, it is within the sole responsibility of the user to set up the specific additional technical features (e.g., Storage Cluster), redundancies, and operational conditions as required to ensure such high availability or failsafe performance.
Security	The properties of the product provide a baseline for product security and therefore end-customer IT security. However, these properties are not sufficient on their own to protect the product from all existing threats, such as intrusion attempts, data exfiltration and other forms of cyberattacks. To customize security settings, please use the configuration options as available for the respective product. During operation, the IT security of this product is within the responsibility of the respective administrator/end-user of the product. Please note, that Fujitsu as a manufacturer does not make any policy prescriptions or advocacy statements regarding IT security best practices and/or general product operation.

Warranty

Manufacturer warranty period	3 years
Warranty type	Onsite warranty
Warranty Terms & Conditions	www.fujitsu.com/support
Product Support - the perfect extension	
Support Pack Options	9x5, 4h Onsite Response Time (depending on country) 9x5, Next Business Day Onsite Response Time 24x7, 4h Onsite Response Time (depending on country)
Recommended Service	24x7 Onsite Service with 4h Onsite Response Time
Service Lifecycle	at least 5 years after shipment, for details see https://support.ts.fujitsu.com/
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/

More information

Fujitsu products, solutions & services

In addition to PRIMERGY GX2570 M6, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/

Software

www.fujitsu.com/software/

More information

Learn more about PRIMERGY GX2570 M6, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

<http://www.fujitsu.com/fts/products/computing/servers/primergy/rack/>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <https://www.fujitsu.com/global/about/resources/terms/>
Copyright 2024 Fujitsu LIMITED

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering. The product was developed for normal business use.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact
Fujitsu LIMITED

Website: www.fujitsu.com
2024-08-26 WW-EN