

# Data Sheet

## Fujitsu PRIMERGY TX1320 M4 Server

Ultra-compact advanced server to grow your business

### PRIMERGY TX1320 M4

The unique ultra-compact FUJITSU Server PRIMERGY TX1320 M4 has advanced technology ideal for most industry verticals, small and medium-sized enterprises (SME), space-constrained environments, retail premises or branch offices. The performance-oriented yet cost-effective mono-socket design supports the latest Intel® Xeon® E-2200/E-2100 product family processors, affordable Intel® Core™ i3 and Pentium® processor options plus up to 128GB RAM at 2,666 MT/s to boost performance for appropriately sized standard business workloads, including virtualized ones (such as: File/Print, Email, ERP/CRM, Messaging, Centralized data storage) and industry specific applications. The new processors with higher core counts, higher speed plus the doubled memory capacity, extend the capability of mono-socket servers to address workloads which hitherto may have required more expensive units. Institutions with special legal requirements such as medical, governmental, legal, or financial offices can benefit from the server's secure and robust storage and transmission features, which include up to eight high quality 2.5-inch storage devices (including up to four ultra-fast NVMe devices for demanding applications), powerful RAID controllers, versatile and affordable backup and networking options together with TPM 2.0 capability. High efficiency (94%), redundant power supplies and the innovative Fujitsu Battery Backup Unit enhance reliability and protect customer investment. This ultra-compact, silent server with the Advanced Thermal Design Technology is designed for deployment flexibility – it can be deployed in offices, on shelves, industrial areas and even on desks at temperatures from 5 °C to 45 °C. New generation technologies include M.2 modules for efficient OS installation along with

Dual microSD capability for VMware ESXi, plus the latest USB 3.1 Gen 2 ports. The TX1320 M4 server also features the iRMC S5, Fujitsu ServerView suite, and the free ISM Essential license. These enable easy, effective management across the server's deployment, installation and administration.

Note: Check the product configurator for the server compatible components currently available at launch.



# Features & Benefits

| Main Features   | Benefits  |
|---|---|
| <p>Ultra-compact server with advanced technology to drive workload performance</p> <ul style="list-style-type: none"> <li>Wide choice of the Intel® Xeon® E-2200/E-2100 product family processors and affordable Core™ i3, Pentium® and Celeron® options. Up to 128GB DDR4 ECC memory (4 DIMMs at 2,666 MT/s) is supported for high-speed, reliable performance. Note: Celeron® available only via special release request. The server also features 8 x hot-plug 2.5-inch storage (SAS/SATA) devices (including up to 4x NVMe) plus RDX backup. Powerful SAS 3.0 RAID Controllers with up to 8 GB cache are also available. Redundant (2x1GbE) LAN as standard, plus 25/10 Gb Ethernet controller options round out the networking capabilities.</li> </ul> <p>Investment protection and flexibility by design</p> <ul style="list-style-type: none"> <li>Future ready with 4x PCIe Gen3 slots, while TPM 2.0 support and Fujitsu's secure 3-way lock secure the data. The server's flexible design also boosts user efficiency: it supports 2x M.2 modules: 1x SATA; 1x NVMe/SATA, plus Dual microSD modules, also offers new 3.1 Gen2 USB ports (Total of 2x 3.1 Gen2 plus 2x 3.1 Gen1, 4x 2.0, Internal 2x 3.1 Gen1 ports).</li> </ul> <p>Improved economics with energy efficiency and reliability</p> <ul style="list-style-type: none"> <li>High efficiency 450W power supplies (94% efficiency) are available with both hot-plug capability and redundancy. Fujitsu Battery Backup Unit, an optional Internal UPS in modular PSU form-factor, 5 years lifetime, fully integrated.</li> </ul> <p>Deploy anywhere, manage and service easily</p> <ul style="list-style-type: none"> <li>The server has an ultra-small form factor with silent operation. It also fields a comprehensive software management suite with the iRMC S5, the Fujitsu ServerView Suite. Plus, the ISM Essential server management suite is available free of charge. The server is designed for enhanced serviceability with easy, fast and comfortable access to critical components.</li> </ul> | <ul style="list-style-type: none"> <li>With the latest compute and memory technology the server can handle appropriately sized, individual or virtualized standard business workloads (file/ print, web, email, messaging, ERP/CRM), or more demanding industry specific applications. The new Intel® Xeon® E-2200 product range's higher core counts and speeds, plus the doubled memory capacity, extends the growth potential of the mono-socket form factor. The flexible storage lets the server handle low-latency storage applications or offer cost-effective storage with backup capability. With up to 8 storage devices, the server can handle most small office dataset or data consolidation requirements. Dual LAN support offers reliable data connectivity for standard requirements right out of the box, while advanced higher data-rate options can support virtualized environments or centralized data sharing over the network.</li> <li>The PCI slots ensure your server grows with your business. You can add advanced Fujitsu RAID controllers for reliable data handling (high grade SAS 3.0 with up to 4/8 GB cache) or networking options (including 10/25Gb Ethernet controllers) for high-speed data transmission. The security features protect valuable enterprise data from unauthorized access - ideal for institutions with legal requirements for high-security data storage. M.2 devices are designed for flexible boot requirements – they offer the option of cost-effective and reliable mirrored SATA modules or deploying high-speed NVMe, while Dual microSD modules offer mirrored support for VMware ESXi. New high data rate USB is suited for the latest generation peripheral devices.</li> <li>Good for the environment, and your business economics – the high efficiency, redundant power supplies offer enhanced reliability and lower energy expenditure. A cost optimized alternative to power supply redundancy, the Battery Backup Unit protects your valuable investment by supporting safe power down and expanded time of operation in case of power loss.</li> <li>The design fits almost everywhere, saves space - ideal for space constrained environments. Low noise emissions, expanded range of operation (5 °C to 45 °C) with Fujitsu's Cool-safe® Advanced Thermal Design technology make it ideal for offices, showrooms and even industrial environments –without expensive cooling. The iRMC S5, Fujitsu ServerView suite simplify the IT administrator's burden, which enable installation and deployment, permanent status monitoring and control. ISM Essential offers converged infrastructure monitoring, server management free of cost. For easy serviceability, the server has a screw-less chassis with hot-plug 2.5-inch devices, hot-plug power supplies and "Easy Rails" for 3.5-inch disks.</li> </ul> |

# Technical details

## PRIMERGY TX1320 M4

### Mainboard

|                               |   |
|-------------------------------|---|
| Mainboard type                | D3673   |
| Chipset                       | Intel® C246   |
| Processor quantity and type   | 1 x Intel® Xeon® E-2200 processor family / Intel® Xeon® E-2100 processor family / Intel® Pentium® processor / Intel® Core™ i3 processor                             |
| Memory slots                  | 4   |
| Memory slot type              | DIMM (DDR4)   |
| Memory capacity (min. - max.) | 4 GB - 128 GB   |
| Memory protection             | ECC   |
| Memory notes                  | Mix and match possible; with dual channel operation better performance (2 modules with equal capacity necessary). Single channel (1 module) configuration possible. |

### Interfaces

|                       |  |
|-----------------------|--|
| USB 2.x ports         | 4 (4x external rear)   |
| USB 3.x ports         | 4 (2x internal, 2x external front, USB 3.0 is now known as USB 3.1 Gen 1). Server also has 2x external rear USB 3.1 Gen 2 ports              |
| Graphics (15-pin)     | 1 analog graphics interface derived from iRMC (up to 1600x1200 or 1920x1080 at 16bpp)  |
| Serial 1 (9-pin)      | 1 serial RS-232-C  |
| LAN / Ethernet        | 2 x1 Gb/s Ethernet; RJ45   |
| Management LAN (RJ45) | 1 x dedicated management LAN port for iRMC S5 (10/100/1000 Mbit/s)<br>Management LAN traffic can be switched to shared onboard Gbit LAN port |

### Onboard or integrated Controller

|                               |  |
|-------------------------------|--|
| RAID controller               | Optionally integrated RAID 0/1 or RAID 5/6 controller for SAS base units (occupies one PCIe slot).<br>All hardware storage controller options are described under Components |
| SATA Controller               | Intel® C246, 2 ports used for accessible drives  |
| SATA controller type notes    | 4 port for internal SATA HDDs with RAID 0, 1, 10 for Windows and Linux   |
| LAN Controller                | Intel® i210 onboard<br>2 x 10/100/1000 Mbit/s Ethernet<br>iSCSI, PXE-Boot and WoL are supported  |
| Remote management controller  | Integrated Remote Management Controller (iRMC S5)<br>IPMI 2.0 compatible   |
| Trusted Platform Module (TPM) | TPM 2.0 module (option)  |

### Slots

|                    |  |
|--------------------|--|
| PCI-Express 3.0 x4 | 1 x Low profile notched  |
| PCI-Express 3.0 x8 | 2 x Low profile notched  |
| PCI-Express x1     | 1 x Low profile PCI-Express 3.0  |
| Slot Notes         | In SAS configuration 1x PCI-Express occupied by modular RAID controller. |

### Drive bays

|                                 |   |
|---------------------------------|---|
| Storage drive bays              | 3.5-inch non hot-plug or 2.5-inch hot-plug SAS/SATA or 2.5-inch NVMe drives |
| Storage drive bay configuration | Not upgradeable in the field.   |
| Accessible drive bays           | 1 x 3.5/1.6-inch for backup devices<br>1 x 5.25/0.5-inch for CD-RW/DVD      |

### Fan Configuration

|                |  |
|----------------|--|
| Number of fans | 3  |
| Fan notes      | Processor fan, rear fan, drive fan, additional drive fan if 8x HDD extension is used |

### Operating panel

|                   |   |
|-------------------|---|
| Operating buttons | On/off switch<br>NMI button<br>Reset button |
|-------------------|---|

## Operating panel

|             |   |
|-------------|---|
| Status LEDs | System status (orange / yellow)<br>Identification (blue)<br>Hard disks access (green)<br>Power (orange / green)<br>At system rear side:<br>System status (orange / yellow)<br>Identification (blue)<br>LAN connection (green)<br>LAN speed (green / yellow)<br>CSS (yellow) |
|-------------|---|

## Operating Systems and Virtualization Software

|  |   |
|--|---|
| Certified or supported operating systems and virtualization software | Windows Server 2019 Datacenter  |
|  | Windows Server 2019 Standard  |
|  | Windows Server 2019 Essentials  |
|  | Windows Server Datacenter, version 1809   |
|  | Windows Server Standard, version 1809   |
|  | Hyper-V Server 2016   |
|  | Windows Server 2016 Datacenter  |
|  | Windows Server 2016 Standard  |
|  | Windows Server 2016 Essentials  |
|  | Windows Storage Server 2016 Standard  |
|  | Windows Server Datacenter, version 1709   |
|  | VMware vSphere™ 7.0   |
|  | VMware vSphere™ 6.7   |
|  | VMware vSphere™ 6.5   |
| SUSE® Linux Enterprise Server 12                                     |   |
| Red Hat® Enterprise Linux 8  |   |
| Red Hat® Enterprise Linux 7  |   |
| Operating system release link  |   |
| Operating system notes   | RHEL 7.5 and SLES 15 GA are not supported for the new CPUs including the Intel® Xeon® E-2200 product family |

## Server Management

### Dimensions / Weight

|                         |                   |
|-------------------------|-------------------|
| Floor-stand (W x D x H) | 98 x 399 x 340 mm |
| Dimension notes         | without feet      |
| Weight                  | up to 10 kg       |

## Environment

### Electrical values

|                                     |   |
|-------------------------------------|---|
| Power supply configuration          | 1 x standard, 1 x hot-plug, 2 x hot-plug redundant, 1 x hot-plug + 1 x Fujitsu FJBU internal battery backup unit (depending on Model) |
| Active power (max. configuration)   | 231 W   |
| Apparent power (max. configuration) | 235 VA  |
| Heat emission (max. configuration)  | 831.6 kJ/h (788.2 BTU/h)  |
| Rated current max.                  | 5 A (100 V) / 2.5 A (240 V)   |
| Power supply                        | 250W standard, 90% (Gold efficiency), 100-240V, 50 / 60Hz<br>450W hot-plug, 94% (Platinum efficiency), 100-240V, 50 / 60Hz            |

## Compliance

|         |                    |
|---------|--------------------|
| Product | PRIMERGY TX1320 M4 |
| Model   | PS1320             |

**Compliance**

|                       |  |
|-----------------------|--|
| Global                | CB<br>RoHS (Substance limitations in accordance with global RoHS regulations)<br>WEEE (Waste electrical and electronic equipment)  |
| Germany               | GS   |
| Europe                | CE   |
| USA/Canada            | CSA us<br>ULc/us<br>FCC Class A  |
| Japan                 | VCCI Class A   |
| Russia                | GOST-R   |
| South Korea           | KC   |
| China                 | CCC  |
| Australia/New Zealand | C-Tick   |
| Taiwan                | BSMI   |
| Compliance link       | <a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>  |
| Compliance notes      | * Warning:<br>This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures. |

## Components

|                       |  |
|-----------------------|--|
| <b>Backup Drives</b>  | RDX Drive, 320 GB, 500 GB, 1 TB , 25 MB/s, half height, USB 3.0  |
| <b>Optical drives</b> | Blu-ray Disc™ Triple Writer, (6x BD-RW, 8x DVD, 24x CD), ultraslim, SATA I<br>DVD Super Multi ultra slim , (8x DVD; 24x CD), ultraslim, SATA I |

|   |   |
|---|---|
| Drives  | SSD SATA, 6 Gb/s, 960 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD  |
|   | SSD SATA, 6 Gb/s, 960 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.9 DWPD  |
|   | SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.0 DWPD   |
|   | SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 0.9 DWPD   |
|   | SSD SATA, 6 Gb/s, 480 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD  |
|   | SSD SATA, 6 Gb/s, 480 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.9 DWPD  |
|   | SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.0 DWPD   |
|   | SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 0.9 DWPD   |
|   | SSD SATA, 6 Gb/s, 240 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.4 DWPD  |
|   | SSD SATA, 6 Gb/s, 240 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD  |
|   | SSD SATA, 6 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD   |
|   | SSD SATA, 6 Gb/s, 7.68 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.5 DWPD   |
|   | SSD SATA, 6 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD   |
|   | SSD SATA, 6 Gb/s, 3.84 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.0 DWPD  |
|   | SSD SATA, 6 Gb/s, 3.84 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 1.0 DWPD  |
|   | SSD SATA, 6 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.0 DWPD   |
|   | SSD SATA, 6 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.9 DWPD   |
|   | SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.0 DWPD  |
|   | SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 0.9 DWPD  |
|   | SSD M.2 SATA, 6 Gb/s, 480 GB, non hot plug, enterprise, 1.5 DWPD (Drive Writes Per Day for 5 years)   |
|   | SSD M.2 SATA, 6 Gb/s, 240 GB, non hot plug, enterprise, 1.5 DWPD (Drive Writes Per Day for 5 years)   |
|   | PCIe-SSD SFF, 1 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD   |
|   | HDD SATA, 6 Gb/s, 8 TB, 7,200 rpm, 512e, non hot plug, 3.5-inch, business critical  |
|   | HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical  |
|   | HDD SAS, 12 Gb/s, 900 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise  |
|   | HDD SAS, 12 Gb/s, 600 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise  |
|   | HDD SAS, 12 Gb/s, 300 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise  |
|   | HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED   |
|   | HDD SAS, 12 Gb/s, 2.4 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise, SED   |
|   | HDD SAS, 12 Gb/s, 2.4 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise  |
|   | HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise  |
|   | HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, hot-plug, 2.5-inch, enterprise  |
|   | HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise  |
| SCSI / SAS Controller   | Broadcom® PSAS CP503i LP SAS Ctrl. 12 Gbit/s 8 ports int. PCIe 3.0 x8   |
| RAID Controller   | pre-configured RAID6 Array,   |
|   | pre-configured RAID6+HS Array,  |
|   | pre-configured RAID5 Array,   |
|   | pre-configured RAID5+HS Array,  |
|   | pre-configured RAID1 Array,   |
|   | pre-configured RAID1+HS Array,  |
|   | pre-configured RAID1+0 Array,   |
|   | pre-configured RAID1+0+HS Array,  |
|   | pre-configured RAID0 Array,   |
|   | Fujitsu PRAID EP580i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s, 8 Gbit/s 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 8 GB, Optional FBU based on LSI SAS3516 |
| Fujitsu PRAID EP540i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s, 8 Gbit/s 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 4 GB, Optional FBU based on LSI SAS3516 |   |
| Fujitsu PRAID EP520i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU based on LSI SAS3516           |   |
| Broadcom® PRAID CP500i LP, RAID Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, No FBU support   |   |

---

Graphics add on cards

NVIDIA® Quadro® P400 , 2 GB, N/A, PCIe x16, 3 x miniDP

<STEPTABLE O="PMod\_239737" OT="Product" TT="DS-Server-EU Warranty" VC="INT - eng" VO="stibo.10560277" W="Main"/>

---

Warranty

Manufacturer warranty period 1 year

Warranty type Onsite Service

Product Support - the perfect extension

Support Pack Options Globally available in major metropolitan areas:  
9x5, Next Business Day Onsite Response Time  
9x5, 4h Onsite Response Time (depending on country)  
24x7, 4h Onsite Response Time (depending on country)

Recommended Service 24x7, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner.

Service Weblink <http://ts.fujitsu.com/Supportservice>

# More information

## Fujitsu platform solutions

In addition to Fujitsu PRIMERGY TX1320 M4, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

## More information

To Learn more about Fujitsu PRIMERGY TX1320 M4, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
<http://ts.fujitsu.com/Primergy>

## Fujitsu green policy innovation

## Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see [http://ts.fujitsu.com/terms\\_of\\_use.html](http://ts.fujitsu.com/terms_of_use.html)

Copyright © Fujitsu Technology Solutions

## Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

## Contact

FUJITSU LIMITED  
Mies-van-der-Rohe-Straße 8  
80807 München  
Germany  
Website: [www.ts.fujitsu.com](http://www.ts.fujitsu.com)  
2024-08-26 CE-EN