

A Smarter Way for Your Broadband Life

Huawei EG8245Q, an intelligent routing-type ONT

Smart
service

Smart
interconnection

Smart O&M



Device Parameters

Dimensions (Hx W x D)	32 mm x 188 mm x 143 mm (without external antenna and pads)
Weight	About 320 g
Operating temperature	0°C to +40°C
Operating humidity	5% RH to 95% RH (non-condensing)
Power adapter input	100-240 V AC, 50/60 Hz
System power supply	11–14 V DC, 1.5 A
Static power consumption	5.2 W
Max. power consumption	18 W
NNI	GPON
UNI	2POTS + 4GE + 2.4G/5G Wi-Fi + 1USB
Optical Connector	SC/APC
Indicators	POWER/PON/LOS/LAN/TEL/USB/WLAN/WPS
Installation mode	On the desk, or on the wall
Compliance certification	CE/WiFi

Interface Parameters

GPON Port	<ul style="list-style-type: none"> Class B+ Receiver sensitivity: -27 dBm Overload optical power: -8 dBm Wavelengths: US 1310 nm, DS 1490 nm Wavelength blocking filter (WBF) of G.984.5 Flexible mapping between GEM Port and TCONT GPON: consistent with the SN or password authentication defined in G.984.3 Bi-directional FEC SR-DBA and NSR-DBA Type B (single-homing& dual-homing)
Ethernet Port	<ul style="list-style-type: none"> Ethernet port-based VLAN tags and tag removal 1:1 VLAN, N:1 VLAN, or VLAN transparent transmission QinQ VLAN Limit on the number of learned MAC addresses MAC address learning Auto-adaptive 10 Mbit/s, 100 Mbit/s or 1000 Mbit/s
POTS Port	<ul style="list-style-type: none"> Maximum REN: 4 G.711A/μ, G.729a/b and G.722 encoding/decoding T.30/T.38/G.711 fax mode DTMF Emergency calls (with the SIP protocol)
USB Port	<ul style="list-style-type: none"> USB2.0 FTP-based network storage File/Print sharing based on SAMBA DLNA function
WLAN	<ul style="list-style-type: none"> IEEE 802.11 b/g/n (2.4G) IEEE 802.11 a/n/ac (5G) 3 × 3 MIMO (2.4G&5G) Antenna gain: 2 dBi WMM/Multiple SSIDs/WPS 2.4G&5G concurrent Air interface rate: 450 Mbit/s (2.4G); 1300 Mbit/s(5G)

Product Function

Smart interconnection

- Smart Wi-Fi coverage
- SIP/H.248 auto-negotiation
- Any port any service
- Parental control
- L2/L3(IPv4) forwarding: 1G uplink, 2G downlink

Smart service

- Scheduled Wi-Fi shutdown
- Smart Wi-Fi sharing:
Portal/802.1x authentication
SoftGRE-based sharing
- Association of one account with two POTS ports

Smart O&M

- IPTV video quality diagnosis
- eMDI
- Rogue ONT detection and isolation from the OLT
- Call emulation, and circuit test and loop-line test
- PPPoE/DHCP simulation testing
- WLAN emulation
- eSight management

Layer 3 Features

- PPPoE/Static IP/DHCP
- NAT/NAPT
- Port forwarding
- ALG, UPnP
- DDNS/DNS server/DNS client
- IPv6/IPv4 dual stack, and DS-Lite
- Static/Default routes
- Multiple services on one WAN port

Multicast

- IGMP v2/v3 proxy/snooping
- MLD v1/v2 snooping

Humanized design

- Support one button to turn off all LEDs

QoS

- Ethernet port rate limitation
- 802.1p priority
- SP/WRR/SP+WRR
- Broadcast packet rate limitation

Security

- SPI firewall
- Filtering based on MAC/IP/URL addresses

Common O&M

- OMCI/Web UI/TR069
- Variable-length OMCI messages
- Dual-system software backup and rollback

Power Saving

- Indicator power saving
- COC V5

