


LEADING TO THE SMART NEW LIFE

Smart Service/Smart O&M/Smart Connection
Huawei Smart Bridge ONT HG8010H



Network Diagram



Key Features

GPON Features:

- Class B+ optical module
- Security authentication mode: SN, password or SN+password
- Upstream/downstream FEC
- GEM port mapping mode: VLAN, 802.1p, VLAN+ 802.1p, IPToS, physical port

Smart O&M:

- Passive+ Active Double levels rouge ONT isolation methods

- Smart protection on remote upgrading
- Smart remote service diagnosis: OPM , PPPoE Dialing simulation,
- Local WEB management and remote NMS management
- Smart power saving

Multicast Features:

- IGMP V2&V3 Snooping
- Dynamic controllable multicast

Ethernet Features:

- Vlan filtering and Vlan transparent transmission
- VLAN N:1 aggregation and VLAN 1:1 translation

Reliability:

- Software Dual-system protection
- Li-battery backup solution and Ni-MH battery backup solution

Product Specification



Ports	1GE
Optical interface	SC/APC
Dimensions(W x D x H)	117mm x 95mm x 27 mm
Power supply	Adapter output: 11-14V DC , 1A
	Adapter input: 100V~240V AC, 50Hz~60Hz
Operating environment	Temperature: 0°C~+40°C
	Humidity: 5%~95%, non-condensing
Average power consumption	4w

Copyright © Huawei Technologies Co., Ltd. 2013. All rights reserved.

THIS DOCUMENT IS FOR INFORMATION PURPOSE ONLY, AND DOSE NOT CONSTITUTE ANY KIND OF WARRANTIES.

HUAWEI TECHNOLOGIES CO., LTD.

Huawei Industrial Base
Bantian Longgang
Shenzhen 518129, P.R. China
Tel: +86-755-28780808

www.huawei.com